



SABRUD CONSORTIUM LTD

Hex Cell



Model Number	SAB 101
Measurement	Single Phase Two Wire
Voltage	240V
Frequency	50Hz
Accuracy	Class1.0
Current:	5(60)A
Starting Current	=0.004Ib(Class 1.0)
Communication	PLC, Optical Port
Burden in Voltage	=2W, 10VA
Burden in Current	=2.5VA
Display Type	LCD
Measuring Energy	0 - 999999.99kWh
Digits	(6+4, 7+3, 8+2, 9+1)
Battery Capacity	=1200mAh
RTC Battery	3.6VDC
Data Storage	=10 Years
Operating Temper-	-40? ~ +70?
Humidity	=95%

Model Number	SAB 101
Measurement	Single Phase Two Wire
Voltage	240V
Frequency	50Hz
Accuracy	Class1.0
Current:	5(60)A
Starting Current	=0.004Ib(Class 1.0)
Communication	PLC, Optical Port
Burden in Voltage Circuit	=2W, 10VA
Burden in Current Circuit	=2.5VA
Display Type	LCD
Measuring Energy Range	0 - 999999.99kWh
Digits	(6+4, 7+3, 8+2, 9+1)
Battery Capacity	=1200mAh
RTC Battery	3.6VDC
Data Storage	=10 Years
Operating Temperature	-40°C ~ +70°C
Humidity	=95%

Sab 101

